

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Full Synthetic Multi-Vehicle Automatic Transmission Fluid, Low Viscosity  
**Product Code:** 900  
**Chemical Name:** Full Synthetic Automatic Transmission Fluid  
**Chemical Family:** Lubricant, Petroleum hydrocarbon  
**Product Use:** Automatic Transmissions  
**Manufacturer:** Scot Lubricants LLC  
**Emergency Telephone Numbers:** 484-619-1393  
6 Horwith Drive Information: 484-275-7990 8am-5pm EST M-F  
Northampton, PA 18067

2. HAZARD IDENTIFICATION

This material is not considered hazardous by OSHA Hazard Communication Standard 29 CFR 1910.1200  
**Classification of the substance or mixture** Not Classified.

**GHS label elements**

Signal word No Signal Word Not Hazardous  
Hazard Statements No know significant effects or critical hazards

**Precautionary statements**

General Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Prevention P273 Avoid release into the environment.  
Response P391 Collect Spillage  
Storage Not Applicable  
Disposal P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Other Hazards**

The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Wt. Percent	Component	Synonym	CAS#
0-90	Hydrotreated Distillate, Heavy Paraffin	Highly Refined Synthetic Base Oil	64742-54-7
0-90	Hydrotreated Distillate, Light Paraffin	Highly Refined Synthetic Base oil	64742-55-8
3 – 7	Mineral Oil	N/A	Mixture
1 – 3	Methacrylate copolymer	N/A	Proprietary
0.5 – 1.20	Alkoxy Sufolane	N/A	Proprietary
0.5 – 1.20	Long-chain alkenyl succinimide	N/A	Proprietary

4. FIRST AID MEASURES

**INHALATION:** Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

**EYE CONTACT:** If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, flush with water for at least 15 minutes. If irritation persists, obtain medical assistance.

**SKIN CONTACT:** Remove affected clothing and shoes. Wash with soap and water until no odor remains. Get medical attention if irritation or pain develops or persists. If product is injected under pressure into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, a physician should

immediately evaluate the individual as a medical emergency. Wash clothing before reuse.

**INGESTION:** Do NOT induce vomiting. Immediately get medical attention. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything to an unconscious person by mouth.

**NOTE TO PHYSICIANS:** Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident.

## 5. FIRE FIGHTING MEASURES

**FLASHPOINT (METHOD):** 248°F (120°C) (minimum) (Closed cup Pensky-Martens)

**FLAMMABLE LIMITS IN AIR:** N/A

**AUTO-IGNITION TEMP:** N/A

**HAZARDOUS COMBUSTION PRODUCTS:** Decomposition and combustion materials may be toxic. Burning may produce sulfur oxides, aldehydes, ketones, carbon monoxide and unidentified organic compounds.

**CONDITIONS OF FLAMMABILITY:** Sparks or flame. Product may burn, but does not ignite readily.

**EXTINGUISHING MEDIA:** Water spray, water fog, dry chemical, carbon dioxide (CO<sub>2</sub>), foam. Water or foam may cause frothing.

### HAZARD RATING

0 = LEAST  
1 = SLIGHT  
3 = MODERATE  
4 = HIGH  
5 = EXTREME

### NFPA 704 HAZARD IDENTIFICATION

HEALTH HAZARD (BLUE)	1
FIRE HAZARD (RED)	1
REACTIVITY (YELLOW)	0
SPECIFIC HAZARD (WHITE)	

**PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:** A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

**FIRE FIGHTING INSTRUCTIONS:** Keep storage containers cool with water spray.

**FIRE AND EXPLOSION HAZARDS:** Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

## 6. ACCIDENTAL RELEASE MEASURES

**SPILLS OR LEAKS:** Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Contain spill. Use personal protective equipment stated in Section 8. Keep unnecessary and unprotected personnel from entering the release area. Ventilate area and avoid breathing vapor or mist. Advise EPA, state agency. Absorb on inert material, shovel, sweep or vacuum spill. For large spills; dike far ahead of liquid spill for collection and later disposal.

## 7. HANDLING AND STORAGE

**HANDLING:** Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well-ventilated area. Avoid contact with eyes, skin, clothing and shoes.

**SHIPPING/STORING:** Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain residue and can be dangerous.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### EXPOSURE GUIDELINES:

#### COMPONENT EXPOSURE LIMITS

##### Hydrotreated Distillate, Heavy Paraffin

ACGIH: 5mg/m<sup>3</sup> TWA (related to Oil mist if generated)  
10 mg/m<sup>3</sup> (related to Oil mist, if generated)  
OSHA: 5 mg/m<sup>3</sup> TWA (related to Oil mist, if generated)

##### Hydrotreated Distillate, Light Paraffin

ACGIH: 5mg/m<sup>3</sup> TWA (related to Oil mist if generated)  
10 mg/m<sup>3</sup> (related to Oil mist, if generated)  
OSHA: 5 mg/m<sup>3</sup> TWA (related to Oil mist, if generated)

##### Mineral Oil

ACGIH: 5mg/m<sup>3</sup> TWA (related to Oil mist, mineral)  
10 mg/m<sup>3</sup> STEL (related to Oil mist, mineral)  
OSHA Final: 5mg/m<sup>3</sup> TWA (related to Oil Mist, mineral)

### ENGINEERING CONTROLS:

**VENTILATION:** Provide general ventilation to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below applicable exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT —

**EYES:** Where eye contact is likely, wear safety glasses; contact lens use is not recommended.

**SKIN:** Protective gloves recommended when prolonged skin contact cannot be avoided. Use of natural rubber or equivalent gloves is not recommended. When product is heated and skin contact is likely, wear heat-insulating gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

**RESPIRATOR:** No respiratory protection is normally required. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

**PERSONAL HYGIENE:** Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard leather articles, such as shoes, saturated with these products.

**OTHER:** Where spills and splashes are likely, facilities storing or using these products should be equipped with emergency eyewash and shower, both equipped with clean water, in the immediate work area.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE/ODOR:** RED FLUID/PETROLEUM ODOR.  
**VAPOR PRESSURE:** LESS THAN 0.1 KPA @104° F (40° C)  
**MOLECULAR WEIGHT:** N/A  
**SOLUBILITY IN WATER:** INSOLUBLE  
**EVAPORATION RATE:** N/A  
**RELATIVE DENSITY:** 0.847 g/cm<sup>3</sup> AT 60° F (15.5° C)  
**SPECIFIC GRAVITY:** 0.847 (ESTIMATED) (WATER=1) (APPROXIMATELY)  
**AUTOIGNITION TEMPERATURE:** N/A  
**FLASH POINT:** 248° F (120° C) (MINIMUM) (CLOSED CUP PENSKY-MARTENS)  
**FLAMMABLE LIMITS IN AIR:** LOWER: N/A UPPER: N/A

**BOILING POINT:** N/A  
**MELTING POINT:** N/A  
**PACKING DENSITY:** N/A  
**OCTANOL/WATER COEFF:** N.D.  
**ODOR THRESHOLD:** N/A  
**VAPOR DENSITY:** >1 (AIR=1)  
**pH:** N/A  
**FLAMMABILITY:** N/A

---

## 10. STABILITY AND REACTIVITY

---

**STABILITY:** Stable under normal temperatures and pressures.

**INCOMPATIBLE MATERIALS:** Avoid oxidizing agents and reducing agents.

**REACTIVITY:** Polymerization is not known to occur under normal temperatures and pressures. Not reactive in water.

**CONDITIONS TO AVOID:** Avoid sparks and open flames.

**HAZARDOUS DECOMPOSITION:** None under normal temperatures and pressures. Also see Section 5: HAZARDOUS COMBUSTION PRODUCTS.

---

## 11. TOXICOLOGICAL INFORMATION

---

### **ROUTES OF EXPOSURE: SKIN, EYES, INGESTION, AND INHALATION**

**ACUTE EFFECTS:** May be harmful if swallowed. May irritate eyes and skin. May cause throat irritation, nausea, vomiting and diarrhea. Aspiration hazard: breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

**REPEATED DOSE EFFECTS:** Prolonged or repeated inhalation or oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

**SENSITIZATION:** Based on best current information, there is no known human sensitization associated with this product.

**MUTAGENICITY:** Based on best current information, there is no known mutagenicity associated with this product.

**CARCINOGENICITY** – Based on best current information, there is no known carcinogenicity as regulated by OSHA; as categorized by ACGIH A1 of A2 substances; as categorized by IARC Group 1 Group 2A. or Group 2B agents as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

**REPRODUCTIVE TOXICITY** – No information available.

**TERATOGENICITY** – No information available.

**NEUROTOXICITY** – High vapor/aerosol concentrations (attainable only at elevated temperatures) may cause central nervous system effects such as dizziness, drowsiness or headaches.

### **TOXICITY DATA:**

#### **Component Analysis – LD50/LC50**

##### **Hydrotreated Distillate, Heavy Paraffin**

Oral LD50>5 g/kg

Dermal LD50>2 g/kg

Inhalation LC50>5 mg/L (mist)

##### **Hydrotreated Distillate, Light Paraffin**

Oral LD50>5 g/kg

Dermal LD50>2 g/kg

Inhalation LC50>5 mg/L (mist)

##### **Mineral Oil**

Dermal LD50 Rabbit >5000 mg/kg

Oral LD50 Rat >5000 mg/kg

Inhalation LC50 Rat .2.18 mg/l (Vapor)

##### **Alkoxy Sulfonane**

Dermal LD50 Rabbit 4000 to 8000 mg/kg

Oral LD50 Rat >1000 mg/kg

**Long-chain alkenyl succinimide**

Dermal LD50 Rabbit 5000 mg/kg

Oral LD50 Rat >14430 mg/kg

---

## 12. ECOLOGICAL INFORMATION

---

**ECOTOXICITY** - Material may be harmful to aquatic organisms. May cause long term adverse effects in aquatic environments.

**PERSISTENCE/DEGRADABILITY** – Not readily biodegradable.

**BIOACCUMULATIVE POTENTIAL** - No information available for this product.

**MOBILITY IN ENVIRONMENT** – Base oil component(s) – Low solubility and floats; expected to migrate from water to land.

**OTHER ADVERSE EFFECTS** – N/A

**OCTANOL/WATER PARTITION COEFFICIENT** – N/A

**VOLATILE ORGANIC COMPOUNDS** - Negligible

**AQUATIC RELEASE** - Advise authorities if product has entered or may enter watercourses or sewer drains.

---

## 13. DISPOSAL INFORMATION

---

**DISPOSAL:** Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

**USEPA WASTE CODES:** This product, if discarded, is not expected to be a characteristic or listed hazardous waste. If recycled in the USA, it must be managed in accordance with 40 CFR Part 279. Processing, use, or contamination by user may change the waste code(s) applicable to the disposal of this product.

---

## 14. TRANSPORTATION INFORMATION

---

**DOT**

**PROPER SHIPPING NAME:** Petroleum Lubricating Oil

**HAZARD CLASS:** Not regulated

**ID NUMBER:** Not regulated

**LABEL REQUIRED:** Not regulated

**EMERGENCY RESPONSE GUIDE NUMBER:** N/A Reference North American Emergency Response Guidebook.

**IATA:** Not regulated

---

## 15. REGULATORY INFORMATION

---

**TSCA:** All components of this product are listed in **Section 3** are exempted from the TSCA requirements.

**SARA SECTIONS 302 304:** Based on the ingredients listed in **Section 3**, this product does not contain any “extremely hazardous substances” listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

**SARA SECTIONS 311 AND 312 REPORTING:** This product poses the following health hazard(s) as defined in 40 CFR Part 370 and is subject to the requirements of Sections 311 and 312 of Title III of Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard Yes

Delayed (Chronic) Health Hazard	No
Physical Fire	No
Physical Sudden Release of Pressure	No
Physical Reactive	No

**SARA SECTION 313:** This product contains the following chemical(s) subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

**CERCLA:** Based on the ingredients listed in **Section 3**, this product does not contain any “hazardous substances” listed pursuant to the comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4. RQ (Reportable quantity): Phenol: 1000 lbs. (454 kg); Ethylene glycol 5000 lbs. (2270 kg); arsenic 1 lb. (0.454kg); Ethyl acrylate 1000 lbs. (454kg)

**CALIFORNIA:** This product contains a component that list the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm: 2- Propenoic Acid, Ethyl Ester, Arsenic, Ethylene oxide.

---

**16. OTHER INFORMATION**

---

**DATE ISSUED:** February 20, 2015  
**SUPERSEDES:** December 16, 2014  
**REVISION NO.** 1  
**REVISION INFORMATION:** GHS Compliance  
**SDS #:** CODE 900

**SCOT LUBRICANTS LLC**  
**6 HORWITH DRIVE**  
**NORTHAMPTON, PA 18067**  
**484-275-7990**

The information on this form is furnished solely for the purpose of compliance with the OSHA Hazard Communication Standard (29 CFR 1910.1200), and shall not be used for any other purpose. The information herein is given in good faith and is based on data considered accurate. However, no warranty, expressed or implied, is made regarding the accuracy of these data or the results to be obtained from the use thereof. This safety sheet was prepared and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.

---

---