



PRODUCT DATA SHEET

5W-20 CODE: 500

Page | 1 OF 1

Scot Lubricants LLC (Scot) Motor Oils are engine oil formulated using paraffinic base oils and proven performance additive packages. Scot Motor Oils can be used in passenger car applications that require API SJ and earlier performance specifications.

FEATURES

Scot Motor Oils are formulated to provide the general equipment protection:

- Protection from deposits at operating temperatures
- Bearing corrosion protection
- Anti-wear, anti-foam and anti-rust properties
- Good cold-cranking capabilities

APPLICATIONS

- When SJ, SF, SE, SD or SD oils are recommended
- Meets older domestic and foreign car manufacturers' requirements

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails
- Cases

SELECTION

Scot Motor Oils are available in 4 multi-viscosity grades to comply with most passenger car and light duty truck engine applications. Listed below are the physical and chemical characteristics of Scot Lubricants Motor Oils. Follow equipment manufacturer recommendations for specific applications.

SAE GRADE:	5W-20	5W-30	10W-30	10W-40
Product Code	500	501	502	503
Viscosity cSt@40 ⁰ C	49.5	68.5	69.3	103
cSt@100 ⁰ C	8.2	10.2	10.5	14.5
Viscosity Index	157	155	141	145
Gravity, API	32.3	31.5	31.5	31.0