



PRODUCT DATA SHEET

MACMILLAN RING FREE™ SAE 30 SN CODE: 523

Page | 1 OF 1

Macmillan Ring Free™ (Macmillan) SAE 30 Motor Oil is formulated using paraffinic base oils and proven performance additive packages. Macmillan SAE 30 Motor Oil can be used in passenger cars and light duty truck engine applications.

FEATURES

Macmillan SAE 30 is formulated to provide the general equipment protection:

- Protection from deposits at operating temperatures
- Bearing corrosion protection
- Anti-wear, anti-foam and anti-rust properties
- Good cold-cranking capabilities

APPLICATIONS

- When SF, SE, SD, SM or SN oils are recommended
- Meets older domestic and foreign car manufacturers' requirements

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails
- Cases

SELECTION

Macmillan SAE 30 Motor Oil is available in 2 single viscosity grades to comply with most passenger car and light duty truck engine applications. Listed below are the physical and chemical characteristics of Scot Lubricants SAE 30 Motor Oil. Follow equipment manufacturer recommendations for specific applications.

SAE GRADE:	SAE 30 SN	SAE 40 SN UL
Product Code	523	524
Viscosity cSt@40°C	86.11	123.33
cSt@100°C	11	14
Viscosity Index	116	111
Gravity, API	29.97	29