



PRODUCT DATA SHEET

PRIVATE LABEL SYNTHETIC BLEND 10W-40 SM/GF-4 CODE: 533

Page | 1 OF 2

Scot Lubricants' LLC (Scot) Private Label Synthetic Blend 10W-40 Motor Oil will meet or exceed the latest automotive manufacturers' requirements for use in passenger car, SUV and light duty truck gasoline engines. Scot's Private Label Synthetic Blend motor oils show improved high temperature deposit control, oil consumption and fuel economy. Scot's Private Label Synthetic Blend oils are premium motor oils that provide better low temperature pump ability and protection.

Scot's Private Label Synthetic Blend oils are premium quality motor oils formulated from selected superior base oils and advanced additive technology, providing the highest levels of equipment protection available. Scot's Private Label Synthetic Blend oils are the engine oil of choice for passenger cars, light trucks, powerboats, motorcycles, and other stationary and mobile equipment.

FEATURES

Scot Lubricants' Private Label Synthetic Blend Motor Oils are formulated to provide:

- Excellent fuel Economy
- Excellent volatility for low oil consumption
- Excellent protection from deposits at all operating temperatures
- Excellent cold-cranking capabilities
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection
- Advanced varnish and sludge protection
- Superior Synthetic Blend Protection against thermal breakdown. (5W-20 and 5W-30)

APPLICATIONS

Scot's Private Label Synthetic Blends, although not licensed, meet current and previous API service classifications: API SM, SL, SJ, SH, SG, SF and ILSAC GF-4, GF-3, GF-2 and GF-1 on applicable viscosity grades Scot's Synthetic Blend oils are recommended for the following uses:

- When Ford WSS-M2C945-A or WSS-M2C946-A is specified.
- When Chrysler MS-6395S is specified.

Scot Lubricants' Private Label Synthetic Blend oils are available to comply with most passenger cars and light duty truck engine applications. Follow equipment manufacturer recommendations for specific applications.



PRODUCT DATA SHEET

PRIVATE LABEL SYNTHETIC BLEND 10W-40 SM/GF-4 CODE: 533

Page | 2 OF 2

SAE GRADE:	5W-20	5W-30	10W-30	10W-40	20W-50
Product Code	530	531	532	533	534
Viscosity cSt@40°C	49.21	63.5	69.3	105.68	153.05
Viscosity cSt@100°C	8.6	10.5	10.5	15.26	18.29
Viscosity, SUS @ 210°F	54	69.8	61.9	78.95	91.29
Viscosity Index	156	155	141	152	134
API Gravity	32.5	31.5	31.5	31.74	29.77
Pour Point: °F	-49	-44	-33	-42	-36

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails