



PRODUCT DATA SHEET

FULL SYNTHETIC 0W-20 SN/GF-5 CODE: 536

Page | 1 OF 2

Scot Lubricants (Scot) Full Synthetic Motor Oil 0W-20 is an advanced formula 100% full synthetic, multi-grade engine oil designed for vehicles operating under severe driving or extreme temperature conditions. It provides improved engine cleanliness and high temperature deposit protection, helps reduce oil consumption and provides exceptional cold flow properties.

Scot's Full Synthetic 0W-20 Oil meets SN/GF in:

- Advanced Wear, Varnish and Sludge Protection
- Superior Protection Against Thermal Breakdown
- Outstanding Resource Conserving Performance

Scot's Synthetic 0W-20 Oil is a premium quality, full synthetic engine oil formulated from selected superior base oils and advanced high performance engine oil additive technology.

Scot's full synthetic engine oil is formulated with low friction additives to help improve fuel economy where SAE 0W-20 is recommended and to provide outstanding engine protection. Scot's synthetic oil meets or exceeds the latest American Petroleum Institute (API) SN-RC and car manufacturers ILSAC GF-5 service classification. Scot's synthetic oils are designed for turbo-charged and high RPM engines which experience high heat. They provide quick flow to critical parts at start up to reduce wear. It is the engine oil of choice for passenger cars, light trucks, powerboats, motorcycles and other stationary and mobile equipment when engine life and performance are important. Scot's synthetic oils meet all previous service classifications: API SN, SM, SL, SJ, SH, SG, SF and ILSAC GF-5, GF-4, GF-3, etc.

Scot's Full Synthetic 0W-20, motor oil is designed especially for turbo-charged and high RPM engines which experience high heat. It provides quick flow to critical parts at start up to reduce wear. Scot's synthetic oils can be use in all services for all gasoline engines, domestic and foreign. Scot's Synthetic Motor Oils are fully compatible with all other synthetic and petroleum based engine oils.

FEATURES

- Excellent protection from deposits at all operating temperatures
- Excellent anti-wear, anti-foam, anti-rust and corrosion protection
- Excellent cold cranking capabilities
- Excellent protection against accelerated oil consumption.



PRODUCT DATA SHEET

FULL SYNTHETIC 0W-20 SN/GF-5 CODE: 536

APPLICATIONS

Scot's Full Synthetic 0W-20 Motor Oil may be recommended for the following uses:

- When SN, SM, SL, SJ, SH, SH, SG, SF, SE, SD or SC oils are required.
- When ILSAC GF-5, GF-4, GF-3, GF-2 oils are required
- When GM 609M is required
- When Ford M2C153H, M2C930-A, M2C929-A(5W-30)
- When DaimlerChrysler MS10797 (5W-20), 10796 (5W-30), 10798 (10W-30), MS6395M
- In gasoline engines and turbo-charged engines

SAE GRADE:	0W-20
Product Code	536
Density, lb./gal.	7.1
API Gravity	35.52
Cold Crank Simulation, mPa/s	6100
Viscosity @40°C, cSt	44.5
Viscosity @ 100°C, cSt	8.46
Viscosity Index	170
NOACK	13.1
Color ASTM	2.5
Water and Sediment (Pass/Fail)	Pass
Appearance	Clear
Pour Point: °C	-48
Flash Point: °C	216

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails