



## PRODUCT DATA SHEET

**HIGH MILEAGE SYNTHETIC BLEND 5W-20 SN CODE: 540**

Page | 1 OF 2

Scot Lubricants' (Scot) High Mileage Synthetic Blend 5W-20 motor oil is an advanced formula blended to meet the requirements of higher mileage engines. As engines age and accumulate 75,000 miles or more, problems such as oil consumption, oil leakage and lower cylinder compression may arise. Most modern engine oils are formulated to meet new car warranty requirements and are not specifically designed to address the needs of higher mileage engines. Scot's High Mileage Synthetic Blend 5W-20 is designed for both.

Scot's High Mileage Synthetic Blend 5W-20 motor oil is comprised of particular additives targeted to offset the effects of high mileage on your engine. Higher mileage engines can experience spark plug fouling, excessive intake valve deposits and sludge build up which may lead to low of power and performance.

Scot's High Mileage Synthetic Blend 5W-20 motor oil is specifically blended engine oil that contains low volatility, which assists in reducing oil consumption, special seal conditioning agents and premium additives for improved wear protection required in new and high mileage engines.

### **FEATURES**

- Minimizes oil consumption
- Maximizes power output
- Conditions engine seals
- Resists thermal breakdown

### **APPLICATIONS**

Scot's High Mileage Synthetic Blend 5W-20 Motor Oil may be applied for the following uses:

- When SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC oils are required
- When ILSAC GF-5, GF-4, GF-2, GF-1 oils are required
- For both older and newer passenger car engines
- For GM Vehicles model years 2011 and after
- When Ford WSS-M2C925-A (5W-30) and WSS-M2C926-A (5W-30) is required
- For Chrysler MS6395S is required



**PRODUCT DATA SHEET**

**HIGH MILEAGE SYNTHETIC BLEND 5W-20 SN CODE: 540**

Page | 2 OF 2

<b>SAE GRADE: High Mileage</b>	<b>5W-20 Synthetic Blend</b>	<b>5W-30 Synthetic Blend</b>	<b>10W-30 Synthetic Blend</b>
<b>Product Code</b>	<b>540</b>	<b>541</b>	<b>542</b>
Viscosity @40°C, cSt	49.21	63.01	68.23
Viscosity @ 100°C, cSt	8.59	10357	10.49
Viscosity, SUS @210°F	54.38	61.25	60.96
Viscosity Index	153	158	141
API Gravity	32.78	33.01	31.51
Pour Point °F	-48	-48	-42

**AVAILABLE IN:**

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails