



PRODUCT DATA SHEET

HD 20W-50 Synthetic Blend CODE 609

Page 1 of 2

Scot Lubricants (Scot) Heavy Duty Synthetic Motor Oils uses premium quality base stocks to meet or exceed the latest automotive manufacturers' requirements. Scots Synthetic Blend 5W-20, 5W-30, 10W-30 and 10W-40 meet and exceed ILSAC GF-5 requirements for use in passenger car, SUV and light duty truck gasoline engines. Scot Synthetic Blend motor oils show improved high temperature deposit control, oil consumption and fuel economy. Scot Synthetic Blend 5W-20, 5W-30, 10W-30, and 10W-40 are synthetic blend, premium motor oils that provide better low temperature pumpability and protection.

Scot Synthetic Blend oils are premium quality motor oils formulated from selected superior base oils and advanced additive technology, providing the highest levels of equipment protection available. Scot Synthetic Blend oils are the engine oil of choice for passenger cars, light trucks, powerboats, motorcycles, and other stationary and mobile equipment.

FEATURES

Scot Synthetic Blend Motor Oils are formulated to provide:

- Excellent fuel Economy
- Excellent volatility for low oil consumption
- Excellent protection from deposits at all operating temperatures
- Excellent cold-cranking capabilities
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection
- Advanced varnish and sludge protection
- Superior Synthetic Blend Protection against thermal breakdown. (5W-20 and 5W-30)
- Meets or exceeds API Resource Conserving (RC) standards, (5W-20, W-30, 10W-30) ILSAC GF-5 Certified.(5W-20, 5W-30, 10W-30)

APPLICATIONS

Scot Synthetic Blend 5W30 meets current and previous API service classifications: API SN, SM, SL, SJ, SH, SG, SF and ILSAC GF-5, GF-4, GF-3. GF-2 and GF-1 on applicable viscosity grades Scot Synthetic Blend oils are recommended for the following uses:

- When Ford WSS-M2C945-A or WSS-M2C946-A is specified.
- When Chrysler MS-6395S is specified.

Scot Synthetic Blend oils are available to comply with most passenger cars and light duty truck engine applications. Follow equipment manufacturer recommendations for specific applications.



SAE GRADE:	5W-30	10W-40	20W-50
Product Code	610	611	609
Viscosity cSt@40°C	63.01	105.68	120
Viscosity cSt@100°C	10.57	15.26	17
Viscosity, SUS @ 210°F	61.25	78.95	85.97
Viscosity Index	158	152	146
API Gravity	33.01	31.74	29.0
Pour Point: °C	-48	-42	-30
Flash Point: °C	230	230	230
Color	3	3	3

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails