



PRODUCT DATA SHEET

HD ISO 10W SYNTHETIC BLEND CODE: 619

Page | 1

Scot Lubricants Heavy Duty Synthetic Blend engine oils use premium quality base stocks and up-to-date additive technology, formulated to provide the highest levels of equipment protection. They are specially formulated for “next generation soot control” to provide excellent performance even in the most severe conditions.

APPLICATIONS:

Normally recommended for aspirated and turbo-charged gasoline and diesel engines. Scots’ Heavy Duty Synthetic Blend engine oils meet or exceed the manufacturers’ requirements for most Ford, General Motors, Mack, Caterpillar, Detroit Diesel, and Cummins engines. Meets MIL-L-2104 specifications.

TYPICAL TEST DATA:

Follow equipment manufacturer recommendations and conventional guides to determine the best oil for specific applications.

ISO SYNTHETIC BLEND	HD 10W	HD 30W	HD 40W	HD 50W
CODE	619	613	616	617
API Gravity	29.5	28	28.1	30
Viscosity CST @ 100 °C	7.0	11.5	14.0	15.5
Viscosity CST @ 40 °F	48.9	86.8	116.8	111.0
Viscosity Index	98.9	122	119	146
Flash Point @°C	>260	>260	>260	>260
Pour Point °C	-35	-20.5	-36	-32