



PRODUCT DATA SHEET

EHD 40W CF CODE 631

PAGE 1 OF 1

Scot Lubricants Extra Heavy Duty 40W CF engine oil is a blend of premium quality base stocks and up-to-date additive technology, formulated to provide the highest levels of equipment protection. It is specially formulated for “next generation soot control” to provide excellent performance in the new EGR (Exhaust Gas Circulation) engines.

APPLICATIONS:

- CI-4, CH-4, CG-4, CF-4, CF, CF-2, CE and CD-II
- SL, SJ, SH, SG, SF, SE, SD or SC
- U.S. Military CID A-A-52306
- MIL-Prf-2104/G or the former MIL-L-46152D
- GM 4718M/6094M
- Detroit Diesel 7SE 270, SERIES 51, 71, 92 and TSB 01-TS-07 engines
- Mack engines (EO-N, EO-M, EO-L Plus, EO-L, EO-K/2)
- Cummins engines CES 20071, 20076, 20078
- Caterpillar drive trains (TO-2), Allison C-3/C-4
- Fuller, Eaton, and Spicer transmissions
- Caterpillar ECF-1

TYPICAL TEST DATA:

Follow equipment manufacturer recommendations and conventional guides to determine the best oil for specific applications.

PRODUCT	EHD 10	EHD 30	EHD 40
CODE	632	630	631
API Gravity	29.5	28	28.1
Viscosity CST @ 100 °C	7.0	11.5	14.0
Viscosity CST @ 40 °F	48.9	86.8	116.8
Viscosity Index	98.9	122	119
Flash Point @°C	>260	>260	>260
Pour Point °C	-35	-20.5	-36