



PRODUCT DATA SHEET

EHD 15W-40CF CODE 635

PAGE 1 OF 1

Scot Lubricants Extra Heavy Duty 15W40CF engine oil is a blend of premium quality base stocks and up-to-date additive technology, formulated to provide the highest levels of equipment protection. It is specially formulated for “next generation soot control” to provide excellent performance in the new EGR (Exhaust Gas Circulation) engines.

APPLICATIONS:

- ◆ CI-4, CH-4, CG-4, CF-4, CF, CF-2, CE and CD-II
- ◆ SL, SJ, SH, SG, SF, SE, SD or SC
- ◆ U.S. Military CID A-A-52306
- ◆ MIL-Prf-2104/G or the former MIL-L-46152D
- ◆ GM 4718M/6094M
- ◆ Detroit Diesel 7SE 270, SERIES 51, 71, 92 and TSB 01-TS-07 engines
- ◆ Mack engines (EO-N, EO-M, EO-L Plus, EO-L, EO-K/2)
- ◆ Cummins engines CES 20071, 20076, 20078
- ◆ Caterpillar drive trains (TO-2), Allison C-3/C-4
- ◆ Fuller, Eaton, and Spicer transmissions
- ◆ Caterpillar ECF-1

TYPICAL TEST DATA:

Follow equipment manufacturer recommendations and conventional guides to determine the best oil for specific applications.

SAE GRADE	EHD 15W-40 CF
Product Code	635
API Gravity	29.0
Viscosity CST @ 100 °C	15.5
Viscosity CST @ 210 °F	81.6
Viscosity Index	135
Temp. °C	-20
Pour Point in °C	-30
Pour Point in °F	-22
Sulfated Ash % Weight	1.2
Total Base Number D2896	10.0