



PRODUCT DATA SHEET

PRIVATE LABEL HYDRAULIC OIL 68

CODE: 713

Page | 1 OF 1

Scot Lubricants LLC (Scot) Private Label Hydraulic Oils contain quality additives that provide excellent anti-wear, rust and oxidation protection.

FEATURES

Scot’s Private Label Hydraulic Oils are formulated to provide general equipment protection:

- Good oxidative and thermal stability – contains thermally stable zinc-type additives.
- Excellent anti-foam and rust protection
- Excellent anti-wear protection for pumps, motors, valves and other hydraulic circuit components.
- Good hydrolytic stability in the presence of water – will not contribute to the formation of corrosive reactants or metal-etching acids.

APPLICATIONS

- Scot’s Private Label Hydraulic Oils may be recommended for application when a quality, anti-wear hydraulic oil is required by equipment manufactures.
- Scot’s Private Label Hydraulic Oils provide excellent vane pump wear and protection. Extremely low pump part weight losses were encountered in the ASTM-D-2882 Vane Pump Wear Tests.

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails

SELECTION

Listed below are the physical and chemical characteristics of Scot’s Hydraulic Oils. Follow equipment manufacturer recommendations and conventional guides to determine the best Hydraulic Oil for specific applications.

VISCOSITY GRADE:	32	46	68
Product Code	711	712	713
Viscosity cSt@40°C	31.0	68.543.7	64.6
Flash, COC °F	428	439	455
Color (ASTM-D-1500)	157	155	141
Oxidation (ASTM-D943)	1500+	1500+	1500
Pour Point, °C	-15	-12	-12
Rust Prevention Test	PASS	PASS	PASS