



PRODUCT DATA SHEET

MACMILLAN RING FREE™ 40W Compressor Oil CODE 763

Page | 1 OF 1

Macmillan Ring-Free™ (Macmillan) 40W Compressor Oil is a high quality, thermally stable, paraffinic mineral based oil. 40W Compressor Oil is an excellent demulsifier, contains anti-wear properties, and protects against rust and corrosion.

APPLICATIONS

- For Single and multi-stage reciprocating air compressors with trunk or crosshead piston systems.
- Suitable for use in combined crankcase and cylinder lubrication systems, or units with separate lubricators.

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums
- 5 Gallon Pails

SELECTION

Listed below are the typical physical and chemical characteristics of Macmillan Ring-Free™ Compressor Oils. Follow equipment manufacturer recommendations and conventional guidelines.

SAE Grade		10W	20W	30W	40W
ISO Grade	32	46	68	100	150
Product Code	764	760	761	762	763
Viscosity cSt@40°C	31	43.7	65	98	148
Viscosity cSt@100°C	5.26	6	8.5	11.0	15.0
Viscosity Index	106	75	100	100	100
API Gravity	31.2	29.1	29.0	28.5	28.0
Pour Point, °C	-15	-12	-9	-6	-6
Flash Point °C	220	226	215	225	230
Sulfur % Weight	.24	.24	.24	.24	.35