



PRODUCT DATA SHEET

UNIVERSAL TRACTOR HYDRAULIC FLUID (303) CODE: 799

Scot Lubricants LLC (Scot) Universal Tractor Hydraulic Oil Fluid 303 (UTHF 303) is a general purpose quality tractor hydraulic fluid blended from highly refined base stocks and formulated for long-term service under severe conditions. UTHF 303 provides protection against anti-wear, PTO clutch, rust protection; extreme pressure properties, water sensitivity, foam suppression and brake chatter reduction. UTHF 303 should be used in ambient temperatures between +32°F and 104°F (0° - 40°C).

Scot’s UTHF 303 may be recommended for: Allis Chalmers®, Allison®, Caterpillar®, Deutz®, Ford® Tractor, International Harvester®, JI Case®/David Brown®, John Deere® 303, J20A, Kubota®, Massey Ferguson®, Oliver®, and White® tractors.

SELECTION

Listed below are the physical and chemical characteristics of Scot Universal Tractor Hydraulic Oil 303.

Always refer to your manufacturer’s manual for specific requirements.

Product Code	799
SAE Grade	20
Viscosity @ 40°C cSt	56.02
Viscosity @ 100°C cSt	9.63
Viscosity Index	148
Flash Point: °F/ °C	400/204
Pour Point: °C	-17
API Gravity °F	30.2

AVAILABLE IN:

- Bulk
- 55 Gallon Drums
- 16 Gallon Quarter Drums